



Application

The EvoLo® 325 cones are the strongest elements in our standard product range to be used under extreme rough conditions. Therefore these cones are used for mounting of engines, bodywork on chassis frames, compressor units, rail cars etc. Most used bearing for shipbuilding and transport industry.

Technical Data

| | | |
|------------------------|-------|-----------------------|
| Maximum load 45° shore | 1000N | Article No. 148632501 |
| Maximum load 60° shore | 1750N | Article No. 148632503 |
| Maximum load 70° shore | 2850N | Article No. 148632505 |

Build in end-limiters

Metal parts: mild steel, corrosion protected by electrolytic galvanization
 Rubber part: highest quality natural rubber

Advantages

- ✓ Height adjustable
- ✓ Easy installation
- ✓ Built in end-limiters protect against overload
- ✓ The use of natural rubber provides best possible vibration isolation.
- ✓ Capable of handling both horizontal and vertical forces
- ✓ Perfect combination between good isolation and secure positioning

Loggers b.v.

Mail: P.O. Box 194
 3300 AD Dordrecht
 The Netherlands

Office: Pieter Zeemanweg 133
 3316 GZ Dordrecht
 The Netherlands

Tel. +31(0) 78 618 28 44
 Fax. +31(0) 78 618 06 50

Email: sales@loggers.nl

Internet: www.loggers.nl

Loggers Schwingungstechnik GmbH
 Am Markt 9
 D-27419 Sittensen
 Germany

Tel. +49(0) 4282 5949 0

Fax. +49(0) 4282 5949 39

Email: sales@loggers.de

Internet: www.loggers.de



LOGGERS

*shock and vibration
 protection is our business*

